



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE

United States Patent and Trademark Office

Address: COMMISSIONER FOR PATENTS

P.O. Box 1450

Alexandria, Virginia 22313-1450

www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
10/796,225	03/09/2004	Takahisa Mizuta	51732/P8-49	2704
23363 7590 05/14/2008 CHRISTIE, PARKER & HALE, LLP PO BOX 7068 PASADENA, CA 91109-7068				
EXAMINER				
DHARIA, PRAEODH M				
ART UNIT		PAPER NUMBER		
2629				
MAIL DATE		DELIVERY MODE		
05/14/2008		PAPER		

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.



UNITED STATES DEPARTMENT OF COMMERCE

U.S. Patent and Trademark Office

Address : COMMISSIONER FOR PATENTS

P.O. Box 1450

Alexandria, Virginia 22313-1450

APPLICATION NO./ CONTROL NO.	FILING DATE	FIRST NAMED INVENTOR / PATENT IN REEXAMINATION	ATTORNEY DOCKET NO.
10796225	3/9/2004	MIZUTA, TAKAHISA	51732/P849

CHRISTIE, PARKER & HALE, LLP
PO BOX 7068
PASADENA, CA 91109-7068

EXAMINER

PRABODH M. DHARIA

ART UNIT	PAPER
----------	-------

2629

20080509

DATE MAILED:

Please find below and/or attached an Office communication concerning this application or proceeding.

Commissioner for Patents

Receipt is acknowledged of papers submitted 04-17-2008 under Information disclosure (PTO 1449) have been placed of record in the file. The PTO 1449 listing have been fully considered and reviewed by Examiner. The signed and initialed copy of the 1449 is attached. The cited prior art on PTO 1449 fails to recite or disclose all the other limitations of independent claims in combination with uniquely distinct features of the claim limitations recited below;

Claims 28-31

"applying a setup pulse for forming a first space charge at a selected discharge cell to the discharge cell; and establishing the first space charge formed by the setup pulse as a priming element, and applying a sustain pulse to the discharge cell, wherein the sustain pulse has a voltage level of a range for discharging the selected discharge cell when the priming element exists in the selected discharge cell."

Claims 1-19 and 21-27

"a single subfield includes an address period for forming wall charges at a discharge cell to be selected from among the discharge cells, and a sustain period for discharging the selected cell, the method comprising: in the sustain period: applying a first pulse to a second electrode of the plurality of second electrodes while a first electrode of the plurality of first electrodes is established at a first voltage; and alternately applying to the first electrodes and the second electrodes a sustain pulse with a second voltage defined by a voltage difference between the first electrodes and the second electrodes, wherein the second voltage is less than a voltage difference between the first pulse and the first voltage."

Claims 32 and 34

"wherein to maximize an efficacy of the plasma display panel a frequency of the sustain pulse supplied for sustaining the discharge cell in the driving circuit is greater than 500KHz and less than or equal to 1MHz due to electromagnetic interference."

/Prabodh M Dharia/
Primary Examiner
Art Unit 2629